

1. **Product type:** MS-IS. MS Hybrid polymer water resistant

2. **Identification:**

Code	Description
MSISG01	MS water resistant Grey 1 kg
MSISG05	MS water resistant Grey 5 kg
MSIST01	MS water resistant Terracotta 1 kg
MSIST05	MS water resistant Terracotta 5 kg

3. **Intended use:**

Concrete protection and repair product.  
Suitable for protection against ingress (Principle 2, method 2.3 of EN 1504-9)  
Suitable for moisture control (Principle 2, method 2.3 of EN 1504-9)  
Suitable for increasing the resistivity (Principle 8, method 8.3 of EN 1504-9)

4. **Manufacturer:**

Index Fixing Systems. Técnicas Expansivas S.L.  
C/Segador, nº13  
26006 Logroño, La Rioja, ESPAÑA

5. **Authorized representative:** Not applicable

6. **System of assessment of performance:**

System 4  
System 4: for reaction to fire

7. **Harmonized standard:**

Laboratory: Técnicas Expansivas S.L.  
Performed: Determination of product type  
Under system: 4

8. **European technical assessment:** Not applicable

## 9. Declared performance:

Essential Characteristics	Performance	Test Standard	Harmonised Technical Specification
Permeability to CO <sub>2</sub>	S <sub>D</sub> > 50 m	EN 1062-6	EN 1540-2:2004
Permeability to water vapor	5m; S <sub>D</sub> ; 50m (Clase II)	EN ISO 7783-1 EN ISO 7783-2	
Capillary absorption and permeability to water	W; 0,1 kg/m <sup>2</sup> h <sup>0.5</sup>	EN 1062-3	
Adhesion strength by pull-off test	> 0,8 (0,5) N/mm <sup>2</sup>	EN 1542	
Reaction to fire after application	Clase F	EN 16501-1	
Dangerous substances	Comply with 5.3		

## 10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Reach Directive EC 1907/2006 declaration:

We inform you that Técnicas Expansivas S.L. is classified in the EC 1907/2006 Reach Directive as a downstream-user of substances.

The product supplied does not contain substances classified as SVHC according to the candidate list in a concentration equal or greater than 0.1% (weight / weight).

Material safety data sheet can be requested to the mail address: [info@indexfix.com](mailto:info@indexfix.com).

Signed on behalf of the manufacturer by:



Santiago Reig, Technical Manager

Logroño, 27/02/2024