

Version number 2 (replaces version 1) Printing date 16.03.2023 Revision: 16.03.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

· Trade name: PU-FP

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture
- Modified hardly flammable one-component polyurethane foam gun grade

1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Técnicas Expansivas S.L P.I. La Portalada II c/ Segador 13 26006 Logroño (La Rioja) SPAIN

· Further information obtainable from:

Tel: +34 941 272 131 Fax: +34 941 272 132 email: info@indexfix.com

1.4 Emergency telephone number: - In case of emergency, consult physician

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if inhaled. Acute Tox. 4 H332 Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. Skin Sens. 1 H317 May cause an allergic skin reaction. Carc. 2 H351 Suspected of causing cancer. STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







- · Signal word Danger
- · Hazard-determining components of labelling: diphenylmethanediisocyanate, isomeres and homologues
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

(Contd. on page 2)

Printing date 16.03.2023 Version number 2 (replaces version 1) Revision: 16.03.2023

Trade name: PU-FP

		(Contd. of page 1)
H332	Harmful if inhaled.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H317	May cause an allergic skin reaction.	
H351	Suspected of causing cancer.	
H335	May cause respiratory irritation.	
H373	May cause damage to organs through prolonged or repeated exposure.	
· Precautiona	ary statements	
P102	Keep out of reach of children.	
P201	Obtain special instructions before use.	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ig	nition sources.
	No smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P260	Do not breathe vapours/spray.	
P280	Wear protective gloves/protective clothing/eye protection.	
P284	In case of inadequate ventilation wear respiratory protection (a protection)	tive mask with
	an appropriate gas filter - i.e. type A1 according to standard EN 14387	⁷).
P302+P352	IF ON SKIN: Wash with plenty of water/soap.	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for br	eathing.
P305+P351-	+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove	contact
	lenses, if present and easy to do. Continue rinsing.	
P308+P313	IF exposed or concerned: Get medical advice/attention.	
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C	C/122 °F.
P501	Dispose of container to in accordance with local/regional/national/inte	rnational
	regulation.	
A -1 -1141 1 1	• 4.	

· Additional information:

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. As from 24 August 2023 adequate training is required before industrial or professional use. EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

- · Results of PBT and vPvB assessment Not applicable.
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.1 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 9016-87-9	diphenylmethanediisocyanate,isomeres and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	40-50%
	· ·	l on nogo 2'

(Contd. on page 3)

Version number 2 (replaces version 1) Printing date 16.03.2023 Revision: 16.03.2023

Trade name: PU-FP

	(Con	td. of page 2)
CAS: 13674-84-5	tris(2-chlorisopropyl)-phosphate	5-15%
EINECS: 237-158-7	♦ Acute Tox. 4, H302	
CAS: 115-10-6	dimethyl ether	1-10%
EINECS: 204-065-8	🚸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
Index number: 603-019-00-8		
CAS: 75-28-5	isobutane	1-10%
EINECS: 200-857-2	♦ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
Index number: 601-004-01-8		
CAS: 86675-46-9	Halogenated polyetherpolyol	1-5%
	♦ Acute Tox. 4, H302	
CAS: 74-98-6	propane	1-5%
EINECS: 200-827-9	♠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	-
Index number: 601-003-00-5		

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: Foam
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Carbon monoxide (CO) Nitrogen oxides (NOx)

Hydrogen cyanide (HCN)

- 5.3 Advice for firefighters
- **Protective equipment:** Mouth respiratory protective device.
- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Printing date 16.03.2023 Version number 2 (replaces version 1) Revision: 16.03.2023

Trade name: PU-FP

(Contd. of page 3)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- Further information about storage conditions:

Store in dry conditions.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- · Storage class: 2B
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 115-10-6 dimethyl ether

IOELV Long-term value: 1920 mg/m³, 1000 ppm

(Contd. on page 5)

Printing date 16.03.2023 Version number 2 (replaces version 1) Revision: 16.03.2023

Trade name: PU-FP

(Contd. of page 4)

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

Protective gloves according to EN 374.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

Wear airtight protective goggles EN 166

· Body protection: Protective work clothing EN 13688

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol

· Colour: According to product specification

Odour: Characteristic
Odour threshold: Not determined.

· Melting point/freezing point: Undetermined.

(Contd. on page 6)

Printing date 16.03.2023 Version number 2 (replaces version 1) Revision: 16.03.2023

Trade name: PU-FP

(Contd. of page 5) · Boiling point or initial boiling point and boiling range Not applicable, as aerosol. · Flammability Not applicable. Lower and upper explosion limit · Lower: Not determined. · Upper: Not determined. · Flash point: Not applicable, as aerosol. Ignition temperature: 199 °C Decomposition temperature: Not determined. Not determined. Hq · · Viscosity: Kinematic viscosity Not determined. · Dynamic: Not determined. · Solubility · water: Not miscible or difficult to mix. · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure: Not determined. · Density and/or relative density · Density: Not determined. · Relative density Not determined. · Vapour density Not determined. 9.2 Other information · Appearance: · Form: Aerosol · Important information on protection of health and environment, and on safety. · Auto-ignition temperature: Product is not selfigniting. Explosive properties: Not determined. · Solvent content: · VOC (EC) 16.9 % Change in condition · Evaporation rate Not applicable. · Information with regard to physical hazard classes · Explosives Void · Flammable gases Void · Aerosols Extremely flammable aerosol. Pressurised container: May burst if heated. Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void **Pyrophoric solids** Void Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void Organic peroxides Void

Printing date 16.03.2023 Version number 2 (replaces version 1) Revision: 16.03.2023

Trade name: PU-FP

(Contd. of page 6)

Corresive to metals

· Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Carbon monoxide

Nitrogen oxides (NOx)

Hydrogen cyanide (prussic acid)

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

Harmful if inhaled.

· LD/LC50 values relevant for classification:				
CAS: 115-10-6 dimethyl ether				
Inhalative	LC50/4 h	308 mg/l (rat)		
CAS: 866	CAS: 86675-46-9 Halogenated polyetherpolyol			
Oral	LD50	917 mg/kg (rat)		
CAS: 136	CAS: 13674-84-5 tris(2-chlorisopropyl)-phosphate			
Oral	LD50	3,600 mg/kg (rat)		

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity

Suspected of causing cancer.

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 8)

Printing date 16.03.2023 Version number 2 (replaces version 1) Revision: 16.03.2023

Trade name: PU-FP

(Contd. of page 7)

11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment Not applicable.
- · **PBT**: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European	waste catalogue
08 05 01*	waste isocyanates
16 05 04*	gases in pressure containers (including halons) containing hazardous substances
15 01 10*	packaging containing residues of or contaminated by hazardous substances

- Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA UN1950
- 14.2 UN proper shipping name
- · ADR 1950 AEROSOLS
 · IMDG, IATA AEROSOLS

(Contd. on page 9)

Printing date 16.03.2023 Version number 2 (replaces version 1) Revision: 16.03.2023

Trade name: PU-FP

	(Contd. of page
14.3 Transport hazard clas	ss(es)
ADR	
Class	2 5F Gases.
Label	2.1
· IMDG, IATA	
Class	2.1 Gases.
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazaro	ds:
Marine pollutant:	No
14.6 Special precautions for user Warning: Gases.	
EMS Number:	F-D,S-U
14.7 Maritime transport in bulk according to IMO instruments	
Transport/Additional informatio	on:
· ADR	
Limited quantities (LQ)	11
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) 2020/878

amending Annex II to Regulation (ÉC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

(Contd. on page 10)

Printing date 16.03.2023 Version number 2 (replaces version 1) Revision: 16.03.2023

Trade name: PU-FP

	(Contd. of page 9)
H280 Contains gas under pressure; may explode if heated.	
H302 Harmful if swallowed.	
H315 Causes skin irritation.	
H317 May cause an allergic skin reaction.	
H319 Causes serious eye irritation.	
H332 Harmful if inhaled.	
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H335 May cause respiratory irritation.	
H351 Suspected of causing cancer.	
H373 May cause damage to organs through prolonged or repeated exposure.	
EUH204 Contains isocyanates. May produce an allergic reaction.	
Date of previous version: 16.03.2023	
Version number of previous version: 1	
Abbreviations and acronyms:	
Flam. Gas 1A: Flammable gases – Category 1A	
Aerosol 1: Aerosols – Category 1	
Press. Gas (Comp.): Gases under pressure – Compressed gas Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
Resp. Sens. 1: Respiratory sensitisation – Category 1	
Skin Sens. 1: Skin sensitisation – Category 1	
Carc. 2: Carcinogenicity – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	

- El