

RE-TE

PRODUCT DESCRIPTION

• Watertight trebol rivet

CHARACTERISTICS



- Tri-bulb blind rivets.
- Aluminium head and shaft.
- Includes EPDM washer
- For outside use.
- Used to join rigid and soft materials.
- Excellent watertightness.
- Large contact surface after expansion with good load distribution.
- Adaptable expansion, can be used on oversized drill holes.

APPLICATIONS



PSA-A



PSE-C

For the installation of solar panels on **aluminium coplanar mounting systems** with direct fixing.

The structural components of the solar range that are normally installed are:

- PSA-A, winged aluminium solar profiles for direct fixing.
- **PSE-C**, aluminium solar profile for side mounting.

Extremely reliable joint used for mounting on metal roofs, maintaining watertightness.

BASE MATERIAL/SEALING ACCESSORIES

BASE MATERIAL



Metal sheet



Sandwich panel

SEALING ACCESSORIES



CS-B
Butylene adhesive sealing tape

Ref. **FT_GS_FD_RE-TE_en** Rev: 1 **24/03/23** 1 of **3**



APPLICATION EXAMPLES



Application example 1: mounting of the PSA-A profile




Application example 2: detail showing mounting on sheet metal to test watertightness

1. R	1. RANGE												
ITEM	CODE	РНОТО	DESCRIPTION	DIAMETER	LENGTH	MATERIALS							
1	RETE5220		Watertight trebol rivet	5.2 mm	20 mm	Aluminium	EPDM EPDM						

Ref. **FT_GS_FD_RE-TE_en** Rev: **1 24/03/23 2** of **3**



2. INSTALLATION INFORMATION



			Inst	allation table	2			
Code	Dt Drilled hole diameter (mm)	E Attachment thickness (mm)	Extraction strength (kN)	Shear strength (kN)	Shaft traction strength (kN)	Extraction load PSA-A profile/0.6 mm S280GD sheet stee NRd (kN)		
RETE5220	5.3-5.5	1.6-6.4	2	3	3.4	0.8		
			Inst	allation tools	•			
RM-MA Hand riveter for blind rivets					RM- PA			
					Long arm hand riveter			

FT_GS_FD_RE-TE_en 24/03/23 3 of 3 Ref. Rev: 1