

CONCRETE SCREWS

UNCOVER THEM





INDEX® Concrete Screws are the ideal solution for professionals seeking top performance with quick, simple, and strong installation — for both structural and non-structural elements in cracked and non-cracked concrete (C20/25 to C50/60).

WHY IS IT A GREAT SOLUTION?




Maximum versatility

Allows for 3 different embedment depths.



Low stress on concrete

Can be installed close to edges and between anchors.



Fast installation

Quick setup using only a drill and impact driver.



Removable

Can be unscrewed — perfect for temporary fixings.



Available in short version

Ideal for installations where standard fixings are too long.

ALL-IN-ONE


Complete range suitable for any application. Available in 9 different head styles, 3 coating types, standard and short versions.





HIGHLY VERSATILE

Recommended for fixing structural and non-structural components.



Structural fixings:

- Stadium seating
- Structural beams and columns
- Temporary awnings and signs
- Timber-to-concrete structures
- · Railings and fences, shelving and racks

Non-structural fixings:

- Pipework
- HVAC ducts
- Electrical trays or cabling systems
- Installations in hollow-core concrete slabs
- Installations in precast slab ceilings

TOP GUARANTEES

TH/TX/TF concrete screws are certified to the highest quality standards:

- ETA 20/0046 Option 1 for cracked and non-cracked concrete (C20/25– C50/60).
- ETA 20/0494 For redundant non-structural systems in concrete (≥C20/25) and hollow-core slabs (≥C30/37).
- Fire resistance certified R30–R120.
- Seismic approvals C1 & C2 for structural use in earthquake-prone areas.















SUPERIOR PERFORMANCE

Over 50% higher loads compared to MTH and MTP anchors. Improved load capacities versus MTH anchors across all diameters.



Characteristic tensile resistance values in C20/25 concrete for isolated anchors without edge or spacing effects.
Values refer to concrete failure mode.







Técnicas Expansivas S.L.P. I. La Portalada II, C/ Segador, 13
26006 · Logroño (La Rioja) · SPAIN

T. (+34) 941.272.131 · E. info@indexfix.com www.indexfix.com